

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

**PENDING CLAIMS:**

1 2. (unchanged) An Automatic Call Distribution (ACD) controller arranged to be coupled  
2 through a packet-based network to a plurality of remote telephone stations and one or more  
3 attendant telephone stations, the ACD controller comprising call reception logic that controls  
4 the establishment of telephone sessions between the remote telephone stations and the attendant  
5 telephone stations;

6 wherein the call reception logic operates to receive call initiation signals from a  
7 particular one of the remote telephone stations; to monitor if an attendant availability parameter  
8 is met; if the attendant availability parameter is not met, to send at least one data information  
9 message to the particular remote telephone station via the packet-based network; and, if the  
10 attendant availability parameter is met, to establish an audio channel between the particular  
11 remote telephone station and a particular one of the attendant telephone stations, wherein the  
12 call reception logic further operates to query the capabilities of the particular remote telephone  
13 station prior to sending the data information message, a format for the data information message  
14 being determined based upon the capabilities of the particular remote telephone station.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 3. (unchanged) An ACD controller according to claim 2, wherein the packet-based network is  
2 an Internet Protocol (IP) network and the data information message is transmitted within an IP  
3 packet.

1 4. (unchanged) An ACD controller according to claim 2, wherein the call reception logic  
2 further operates to determine a waiting parameter to be presented to a user at the particular  
3 remote telephone station, the data information message comprising said waiting parameter.

1 5. (unchanged) An ACD controller according to claim 4, wherein the waiting parameter  
2 comprises a number corresponding to an order in which the call initiation signals were received  
3 from the particular remote telephone station with respect to other call initiation signals received  
4 from other ones of the remote telephone stations.

1 6. (unchanged) An ACD controller according to claim 4, wherein the waiting parameter  
2 comprises an estimate of the time before the attendant availability parameter will be met.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 7. (unchanged) An ACD controller according to claim 4, wherein the call reception logic  
2 further operates to update the waiting parameter periodically until the attendant availability  
3 parameter is met and to send further data information signals comprising updated waiting  
4 parameters to the particular remote telephone station via the packet-based network until the  
5 attendant availability parameter is met.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 8. (unchanged) An Automatic Call Distribution (ACD) controller arranged to be coupled  
2 through a packet-based network to a plurality of remote telephone stations and one or more  
3 attendant telephone stations, the ACD controller comprising call reception logic that controls  
4 the establishment of telephone sessions between the remote telephone stations and the attendant  
5 telephone stations;

6 wherein the call reception logic operates to receive call initiation signals from a  
7 particular one of the remote telephone stations; to monitor if an attendant availability parameter  
8 is met; if the attendant availability parameter is not met, to send at least one data information  
9 message to the particular remote telephone station via the packet-based network; and, if the  
10 attendant availability parameter is met, to establish an audio channel between the particular  
11 remote telephone station and a particular one of the attendant telephone stations, wherein the  
12 data information message comprises an alert request option; and

13 wherein the call reception logic further operates to monitor for receipt of an alert request  
14 activation message from the particular remote telephone station in response to the alert request  
15 option; and, if the call reception logic receives the alert request activation message from the  
16 particular remote telephone station, to send an alert on message to the particular remote  
17 telephone station when the attendant availability parameter is met.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 9. (unchanged) An ACD controller according to claim 8, wherein the call reception logic  
2 further operates to periodically determine a waiting parameter prior to the attendant availability  
3 parameter being met and to periodically send a data information message comprising said  
4 waiting parameter to the particular remote telephone station.

1 10. (unchanged) An ACD controller according to claim 8, wherein the call reception logic  
2 further operates to send an alert mode indication to the particular remote telephone station if the  
3 call reception logic receives the alert request activation message from the particular remote  
4 telephone station.

1 11. (unchanged) An ACD controller according to claim 10, wherein the alert mode indication  
2 is an alert mode icon to be displayed on the display of the particular remote telephone station.

1 12. (unchanged) An ACD controller according to claim 8, wherein the alert on message  
2 comprises a ring request for the particular remote telephone station.

1 13. (unchanged) An ACD controller according to claim 12, wherein the ring request comprises  
2 a volume request to ensure a ring volume selection corresponding to the particular remote  
3 telephone station is at a sufficiently high level.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 14. (unchanged) An ACD controller according to claim 8, wherein the alert on message  
2 comprises an email message being sent to an email account corresponding to the particular  
3 remote telephone station.

1 15. (unchanged) An ACD controller according to claim 8, wherein the alert request option  
2 comprises a text string to be displayed on a display screen associated with the particular remote  
3 telephone station, the text string indicating to a user of the particular remote telephone station  
4 how to send an alert request activation message to the call reception logic.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 16. (unchanged) An Automatic Call Distribution (ACD) controller arranged to be coupled  
2 through a packet-based network to a plurality of remote telephone stations and one or more  
3 attendant telephone stations, the ACD controller comprising call reception logic that controls  
4 the establishment of telephone sessions between the remote telephone stations and the attendant  
5 telephone stations;

6 wherein the call reception logic operates to receive call initiation signals from a  
7 particular one of the remote telephone stations; to monitor if an attendant availability parameter  
8 is met; if the attendant availability parameter is not met, to send at least one data information  
9 message to the particular remote telephone station via the packet-based network; and, if the  
10 attendant availability parameter is met, to establish an audio channel between the particular  
11 remote telephone station and a particular one of the attendant telephone stations, wherein [the]  
12 the data information message comprises a plurality of audio options; and

13 wherein the call reception logic further operates to monitor for receipt of one of a  
14 plurality of audio option activation messages from the particular remote telephone station, each  
15 of the audio option activation messages corresponding to a selection of a particular one of the  
16 audio options; and, if the call reception logic receives one of the audio option activation  
17 messages from the particular remote telephone station, to send audio signals associated with the  
18 received audio option activation message to the particular remote telephone station.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 17. (unchanged) An ACD controller according to claim 16, wherein each of the audio options  
2 comprises a text string to be displayed on a display screen associated with the particular remote  
3 telephone station, each of the text strings indicating to a user of the particular remote telephone  
4 station how to send an audio option activation message corresponding to the particular audio  
5 option to the call reception logic.

1 18. (unchanged) An ACD controller according to claim 16, wherein the data information  
2 message comprises a browser request option; and  
3 wherein the call reception logic further operates to monitor for receipt of a browser  
4 request activation message from the particular remote telephone station in response to the  
5 browser request option; and, if the call reception logic receives a browser request activation  
6 message from the particular remote telephone station, to initiate a browser session with the  
7 particular remote telephone station such that the particular remote telephone station can access  
8 data information within a browser format.

1 19. (unchanged) An ACD controller according to claim 18, wherein the browser format is a  
2 web page.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 20. (unchanged) An ACD controller according to claim 18, wherein, if a browser session is  
2 initiated with the particular remote telephone station, the call reception logic further operates  
3 to send an alert message to the particular remote telephone station when the attendant  
4 availability parameter is met.

1 21. (unchanged) An ACD controller according to claim 18, wherein, if a browser session is  
2 initiated with the particular remote telephone station, the call reception logic further operates  
3 to send at least a portion of the data information accessed by the particular remote telephone  
4 station during the browser session to the particular attendant telephone station when establishing  
5 the audio channel between the particular remote telephone station and the particular attendant  
6 telephone station.

1 22. (unchanged) An ACD controller according to claim 18, wherein, if a browser session is  
2 initiated with the particular remote telephone station, the call reception logic further operates  
3 to initiate a browser session with the particular attendant telephone station when establishing  
4 the audio channel between the particular remote telephone station and the particular attendant  
5 telephone station, the browser session being identical to that initiated with the particular remote  
6 telephone station.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1     23. (unchanged) An ACD controller according to claim 18, wherein the browser request option  
2     comprises a text string to be displayed on a display screen associated with the particular remote  
3     telephone station, the text string indicating to a user of the particular remote telephone station  
4     how to send a browser request activation message to the call reception logic.

1     24. (unchanged) An Automatic Call Distribution (ACD) controller arranged to be coupled  
2     through a packet-based network to a plurality of remote telephone stations and one or more  
3     attendant telephone stations, the ACD controller comprising call reception logic that controls  
4     the establishment of telephone sessions between the remote telephone stations and the attendant  
5     telephone stations;

6             wherein the call reception logic operates to receive call initiation signals from a  
7     particular one of the remote telephone stations; to initiate a browser session with the particular  
8     remote telephone station such that the particular remote telephone station can access data  
9     information within a browser format; to monitor for receipt of an attendant request message  
10    being sent from the particular remote telephone station; and, if an attendant request message is  
11    received, to monitor if an attendant availability parameter is met and, if the attendant availability  
12    parameter is met, to establish an audio channel between the particular remote telephone station  
13    and a particular one of the attendant telephone stations.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 25. (unchanged) An Automatic Call Distribution (ACD) system comprising an ACD controller  
2 and one or more attendant telephone stations arranged to be coupled to the ACD controller, each  
3 of the ACD controller and the attendant telephone stations arranged to be coupled through a  
4 packet-based network to a plurality of remote telephone stations, the ACD controller comprising  
5 call reception logic that controls the establishment of telephone sessions between the remote  
6 telephone stations and the attendant telephone stations;

7 wherein the call reception logic operates to receive call initiation signals from a  
8 particular one of the remote telephone stations; to monitor if an attendant availability parameter  
9 is met; if the attendant availability parameter is not met, to send at least one data information  
10 message including softkey option labels to the particular remote telephone station via the  
11 packet-based network; and, if the attendant availability parameter is met, to establish an audio  
12 channel between the particular remote telephone station and a particular one of the attendant  
13 telephone stations.

1 26. (unchanged) An ACD system according to claim 25 further comprising a Local Area  
2 Network (LAN) arranged to be coupled to the packet-based network, each of the attendant  
3 telephone stations being coupled through the LAN to the ACD controller.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 27. (unchanged) A telephone system comprising a packet-based network, an Automatic Call  
2 Distribution (ACD) controller, one or more attendant telephone stations, and one or more  
3 remote telephone stations, each of the attendant telephone stations and remote telephone stations  
4 being arranged to be coupled through a packet-based network to ACD controller, the ACD  
5 controller comprising call reception logic that controls the establishment of telephone sessions  
6 between the remote telephone stations and the attendant telephone stations;

7 wherein the call reception logic operates to receive call initiation signals from a  
8 particular one of the remote telephone stations; to monitor if an attendant availability parameter  
9 is met; if the attendant availability parameter is not met, to send at least one data information  
10 message to the particular remote telephone station via the packet-based network, the at least one  
11 data information message containing option labels for selection of one or more of a music  
12 choice operation, an alert request operation, and a browser request operation; and, if the  
13 attendant availability parameter is met, to establish an audio channel between the particular  
14 remote telephone station and a particular one of the attendant telephone stations.

1 28. (unchanged) A telephone network according to claim 27, wherein the remote telephone  
2 station is a wireless telephone station that is coupled to the packet-based network via a  
3 communication link with a base station that is further coupled to the packet-based network.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 29. (unchanged) Within an Automatic Call Distribution (ACD) controller, a method of  
2 establishing a telephone session between a remote telephone station and an attendant telephone  
3 station via a packet-based network, the method comprising:  
4 receiving call initiation signals from the remote telephone station;  
5 sending at least one data information message containing softkey option labels to the  
6 remote telephone station via the packet-based network;  
7 monitoring if an attendant availability parameter is met;  
8 if the attendant availability parameter is not met, sending at least one data information  
9 message to the particular remote telephone station via the packet-based network; and  
10 if the attendant availability parameter is met, to establish an audio channel between the  
11 particular remote telephone station and a particular one of the attendant telephone stations.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 30. (unchanged) A switching device arranged to be coupled through a telephone network to at  
2 least one remote telephone station and an Automatic Call Distribution (ACD) system  
3 comprising at least one attendant telephone station, the switching device comprising alert-  
4 request logic that is operable when the remote telephone station is connected to the ACD system  
5 through the switching device;

6 wherein the alert request logic operates to monitor for receipt of an alert request  
7 activation signal; and, if the alert request activation signal is received, to store a directory  
8 number corresponding to the remote telephone station, to disconnect the remote telephone  
9 station from the switching device, to monitor for an attendant ready signal from the ACD  
10 system and, if the attendant ready signal is received, to initiate a telephone session with the  
11 remote telephone station using the stored directory number in order to connect the remote  
12 telephone station and the ACD system.

1 31. (unchanged) A switching device according to claim 30, wherein the alert request activation  
2 signal is a sequence of Dual Tone Multi-Frequency (DTMF) signals.

ATTORNEY DOCKET NO. 10628ROUS01U (NORT10-00169)

U.S. SERIAL NO. 09/472,910

PATENT

1 32. (unchanged) A switching device according to claim 30, wherein, in order for the alert  
2 request logic to monitor for receipt of an attendant-ready signal, the alert request logic further  
3 operates to periodically send a recorded voice message to the ACD system indicating how to  
4 send an attendant ready signal to the alert request logic.

1 33. (unchanged) A switching device according to claim 30, wherein the attendant ready signal  
2 comprises a ring back signal that is generated when a telephone call is transferred.

1 34. (unchanged) Within a computing device coupled to a telephone network, a method of  
2 alerting a telephone station that an attendant within an Automatic Call Distribution (ACD)  
3 system is ready for a telephone session, the telephone station being within a telephone session  
4 with the ACD system through the computing device, the method comprising:

5 monitoring for receipt of an alert request activation signal; and

6 if the alert request activation signal is received, storing a directory number corresponding  
7 to the remote telephone station; disconnecting the telephone station from the computing device;  
8 monitoring for an attendant ready signal from the ACD system; and, if the attendant ready  
9 signal is received, initiating a telephone session with the telephone station using the stored  
10 directory number in order to connect the telephone station and the ACD system.

ATTORNEY DOCKET No. 10628ROUS01U (NORT10-00169)

U.S. SERIAL No. 09/472,910

PATENT

1 35. (unchanged) A telephone station arranged to be coupled through a telephone network to an  
2 Automatic Call Distribution (ACD) system comprising at least one attendant telephone station,  
3 the telephone station comprising alert request logic that is operable when the telephone station  
4 is connected to the ACD system;

5 wherein the alert request logic operates to monitor for receipt of an alert request  
6 activation signal; and, if the alert request activation signal is received, to periodically send a  
7 recorded voice message to the ACD system indicating how to send an attendant ready signal  
8 to the alert request logic, to monitor for an attendant ready signal from the ACD system and, if  
9 the attendant ready signal is received, to initiate a alert operation on the telephone station.